



- High Density Denim Sound Dampening Strips
- High Density Denim Batt Insulation
- Simple Installation Process
- Blocks Sound Transfer from Room to Room
- Improves STC Values Up To 3-10 Pts
- R13 Thermal Performance

The **ULTRATOUCH+ SOUND CONTROL SYSTEM** is the first "acoustic system in a bag" and offers an easy to install option for effective sound isolation. UltraTouch+ consists of a high density denim batt insulation and high density sound dampening strips that are placed on all horizontal/vertical framing prior to the installation of finish material. This creates an effective vibration damper between the drywall and studs, helping to stop the transfer of sound between spaces. With a simple installation process, UltraTouch+ is easy for anyone to work with. Improves STC ratings from 3-10 points when compared to traditional batt insulation and offers R13 thermal performance.

| General Information |         |                |            |            |             |         |              |
|---------------------|---------|----------------|------------|------------|-------------|---------|--------------|
| Product Code        | R Value | Thickness (MM) | Width (MM) | Length (M) | Square Feet | Pcs/Bag | Weight (LBS) |
| 10002-11315         | 13      | 3.5" 89        | 15.5" 394  | 94" 2.39   | 80.96       | 8       | 40           |

| Physical Properties             |                             |                   |
|---------------------------------|-----------------------------|-------------------|
| Property                        | Performance                 | Test Method       |
| Surface Burning Characteristics | Flame Spread 5 (Class 1)    | ASTM E-84         |
| Fire Hazard Classification      | Smoke Development (Class 1) | UL 723            |
| Corrosion Resistance            | Passed                      | ASTM C-739        |
| Fungi Resistance                | Passed (No Growth)          | ASTM C-739        |
| Bacteria Resistance             | Passed (No Growth)          | ASTM C-739        |
| Moisture Absorption             | Passed (Less than 15%)      | ASTM C-739        |
| Fire Test of Building Material  | Passed (1Hour Rating)       | ASTM E-119/UL-263 |

### Product Compliances

UltraTouch+ meets the standards and specifications of the following organizations:

BOCA Building Officials and Code Administrators  
 CABO Council of American Building Officials  
 ICBO International Conference of Building Officials  
 LEED Leadership in Energy and Environmental Design

SBCCI Southern Building Code Congress International  
 California Bureau of Thermal Insulation Lic # TL-1367, Reg CA-T367AZ  
 CAL Environmental Spec #1350  
 ICC Report ESR-1134 LARR ICC ER-134

